



HAL
open science

Impact of divertor configuration on recycling neutral fluxes for ITER-like wall H-mode plasmas

E de La Cal, U Losada, A Martín de Aguilera, A Shaw, E Solano, D Alegre, I Balboa, P Carvalho, J Gaspar, I Borodkina, et al.

► **To cite this version:**

E de La Cal, U Losada, A Martín de Aguilera, A Shaw, E Solano, et al.. Impact of divertor configuration on recycling neutral fluxes for ITER-like wall H-mode plasmas. *Plasma Physics and Controlled Fusion*, 2020, 62, pp.035006. 10.1088/1361-6587/ab5fb1 . hal-03150405

HAL Id: hal-03150405

<https://amu.hal.science/hal-03150405>

Submitted on 23 Feb 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Impact of divertor configuration on recycling neutral fluxes for ITER-like wall H-mode plasmas

E. de la Cal¹, U. Losada¹, A. Martín de Aguilera¹, E. Solano¹, D. Alegre^{1,2}, I. Balboa³, P. Carvalho³, J. Gaspar⁵, A. Shaw³, I. Borodkina⁴, S. Brezinsek⁴, D. Douai⁶, C. Giroud³, C. Guillemaut³, C. Hidalgo¹, A. Huber³, E. Joffrin⁶, T. Loarer⁶, E. de la Luna¹, A. Manzanares¹, F. Militello³, L. de Pablos¹, S. Wiesen⁴ and JET contributors *

¹Laboratorio Nacional de Fusión, CIEMAT, Av. Complutense 40, E-28040 Madrid, Spain

²Departamento de Ingeniería Energética, UNED, C/Juan del Rosal 12, E-28040 Madrid, Spain

³CCFE Fusion Assoc., Culham Science Centre, Abingdon, OX14 3DB, UK

⁴Forschungszentrum Jülich, Institut für Energie- und Klimaforschung- und Plasmaphysik, 52425, Jülich, Germany

⁵Aix Marseille Univ, CNRS, IUSTI, Marseille, France

⁶CEA, IRFM, F-13108 Saint-Paul-lez-Durance, France

*See the author list of "X. Litaudon *et al* 2017 *Nucl. Fusion* 57 102001"

E-mail: e.delacal@ciemat.es

Abstract

It is well known since the last years that in JET, with the ITER-like wall, the performance of high-power H-mode plasmas strongly depends on the divertor magnetic topology. This is generally attributed to the effect of the magnetic field shaping on the neutral flux transport and pumping, which determine in high density H-mode plasmas the pedestal properties and finally the global confinement. In the present work we have analysed for different magnetic configurations the spatial distribution and the dynamic behaviour of the D_{α} -emission. Experimental observations indicate that for certain configurations, the surface temperature and the D_{α} -emission anomalously increase on top of the inner divertor, which points to thermal outgassing there. This is the region where most Beryllium co-deposits accumulate and most Deuterium becomes trapped. The overheating at this region far from the strike point (SP) is observed to happen in magnetic configurations with reduced distance between the divertor material surface and the Separatrix (Clearance). The neutral flux that appears at the upper inner divertor during a few milliseconds after the ELM-crash, is by more than an order of magnitude larger than the puffing rate and dominates over the rest of the divertor recycling.

1 Finally, a preliminary study describes how this thermal fuel outgassing from the co-deposited layers could
2 be intentionally used as a Wall-conditioning technique with plasmas that focalise their particle and heat
3 flux there. This could be used as a Wall isotope exchange technique or for Tritium recovery from regions
4 where Be co-deposits accumulate in JET with the ITER-like wall.

5
6 Keywords: Plasma-wall, Recycling, Divertor Configuration, Fuel Trapping, Outgassing, Neutrals

7 8 **1. Introduction**

9
10 Since the installation of the ITER-like wall (ILW), JET has demonstrated successfully the compatibility
11 of an all-metallic wall with reactor relevant high power H-mode scenarios. The benefit is a reduced fuel
12 trapping in the vacuum vessel by at least one order of magnitude with respect to the Carbon divertor [1-4].
13 The latter exhibited a prohibitively large wall fuel accumulation due to the strong chemical reactivity of
14 Carbon with Hydrogen isotopes. The Hydrocarbons generated by the plasma demonstrated to have a high
15 sticking capacity at remote and hidden surfaces producing thick hydrogenated Carbon co-deposits. No
16 reliable cleaning method to remove these deposits was found. The reactor vessel Tritium (T) inventory
17 predicted due to this effect showed that operation was impossible to be maintained under safety limits for a
18 reasonable fusion plasma burning operation time: a few hundred 400 seconds D-T ITER plasmas would
19 have been sufficient to overpass this limit. With such pessimistic predictions, the use of Carbon as plasma
20 facing component for next step burning reactors had to be abandoned and metallic plasma facing
21 components appeared as the alternative. The promising JET-ILW results made the fusion community gain
22 confidence in reactor relevant plasma scenarios with an all-metallic environment and ITER will operate
23 since the beginning with a Beryllium-Tungsten First wall. The originally planed preliminary operation
24 phase with a Carbon divertor has been cut out, thereby reducing costs and time till D-T operation.

25 Moreover, during this last JET period, valuable experience has been gained in plasma operation with an
26 all-metallic wall, which has been shown to have particularities not faced before with the Carbon phase.
27 New “hidden parameters” appear that are being studied in order to understand the physics of H-mode
28 plasmas [see e.g. 3-4]. For example, during the first years of JET-ILW operation, H-mode confinement was
29 sensibly reduced by at least 20% in the so-called ITER Baseline scenario (normalized pressure ratio $\beta_N \approx$
30 1.5) with respect to the Carbon phase. Only with Nitrogen seeding, good confinement could partially be
31 recovered [5]. This degradation was attributed to the large fuel puffing amounts necessary to reduce the
32 plasma edge temperature at the divertor targets to minimise Tungsten sputtering and its subsequent
33 accumulation in the plasma centre. This is believed to be the origin of the pedestal and central plasma
34 temperature decrease and the performance degradation. More recently it was discovered that global
35 confinement could be improved for specific magnetic configurations, with the best performance
36 (confinement factor $H_{98Y} \approx 1$) obtained with the SPs located at the divertor corners near the pumping
37 conducts (here called Corner- or C-configuration), where recycled neutral exhaust is most efficient [6-11,
38 see figure 1].

39 This observation addresses once again to the role of the neutral density (or pressure) on the scrape-off-
40 layer (SOL) plasma. Generally speaking, high neutral densities degrade the pedestal properties and finally

1 the global plasma confinement. Unfortunately, up to date, there is no clear understanding of the physics
2 behind it. Simulations show that energy losses of neutrals entering the confined region are minimised with
3 the SP near the pumping openings at the divertor corners, but the quantitative values don't explain by far
4 the observed differences in confinement [9]. On the other hand, the increase of the main chamber neutral
5 pressure has been linked with the outer SP position distance to the divertor pumping openings at the corner,
6 which affects negatively plasma pedestal pressure [11]. This empirical observation was already disclosed
7 many years ago and the energy confinement time was directly scaled with neutral pressure in the main
8 chamber [see e.g. 12, 13]. A possible explanation of this effect disclosed in [11] links the main chamber
9 neutrals with the radial electric field change that increases the rotational shear at the plasma edge, which
10 finally reduces perpendicular transport. For further bibliography concerning the effect of divertor geometry
11 and magnetic configuration on many different aspects such as the pumping efficiency, target power loads,
12 ionization sources and detachment, etc., the reader is referred to [14]. For modelling aspects of neutrals
13 including molecular dynamics in ITER and its influence on divertor performance the reader is referred to
14 [15] and references therein.

15 On the other hand, since operation with the ITER-like wall, the physics of Recycling has considerably
16 varied. This was something expected due to the very different characteristics of Carbon (C) and Tungsten
17 (W) when exposed to Deuterium (D) fluxes [1, 16-23]. For example W has a much larger reflection
18 coefficient compared to C, and a much lower capacity to adsorb D, except in regions where Beryllium (Be)
19 co-deposits grow. Moreover, Recycling, which is the re-emission by the plasma-facing material of D as
20 response of the ion and heat fluxes, should be seen as a dynamic process if transient events as ELMs are
21 present. Therefore, the physics of ELMy scenarios in the SOL and Edge plasma is a complex kinetic
22 plasma-wall interaction process where the neutral, ion and heat transport must be balanced. Some aspects
23 of the Recycling and pedestal recovery dynamics in JET with the new ITER-like wall have been described
24 recently [see e.g. 19-23]. More generic modelling of the dynamics of the surface response during ELMs can
25 be found in [24-25]. There is also an experimental study on the Recycling coefficient fast variations during
26 ELM-like events in the TJ-II stellarator [26]. Finally, a theoretical study of the fuel absorption and re-
27 emission kinetics has been done for W when exposed to ELMs using a Diffusion-Trapping Model,
28 simulating quantitatively the incident power and particle fluxes [27].

29 In the present work we study the spatial distribution and the dynamic behaviour of the recycling neutral
30 fluxes at the divertor for high-power H-mode plasmas with different magnetic configurations. The total
31 heating power $P > 15$ MW was mainly through Neutral Beam Injection (NBI) with sometimes a small
32 fraction of Ion Cyclotron Range of Frequencies (ICRF) heating. More specifically the effect of the
33 proximity of the SPs to the divertor corners near the pumping conducts is compared for similar plasmas as
34 done in previous studies [6-11]. The main analysis has been done comparing the spatial distribution of the
35 D_α -emission and its dynamics during ELMs at the inner divertor, since the neutral fluxes dominate there for
36 the here studied plasmas.

37 In a previous work it was already observed [22], that for certain magnetic topologies, the D neutral
38 fluxes strongly increase for high power H-mode plasmas on top of the inner divertor just after the ELM-
39 crash. This was initially surprising because this region is relatively far from the SP position. The D
40 emission came from the region where surface analysis has shown that most D becomes trapped within the

1 Be co-deposits that preferentially accumulate there. Therefore we proposed already in [22] that local fuel
2 outgassing due to surface over-heating could be the reason of the increased neutral flux. Also in a recent
3 study, during the change-over from a Deuterium to a Hydrogen campaign, a strong spatial inhomogeneity
4 of the plasma isotope ratio in the divertor was observed [28]. This phenomenon was attributed to local re-
5 emission of the fuel isotope of the previous campaign that was trapped in the Be co-deposits of the inner
6 divertor.

7 The goal of the present work is to try to understand this outgassing phenomenon in more detail.
8 Therefore, we analyse the surface temperature evolution using thermography to show that there is a clear
9 correlation with the D_α -emission increase at this divertor region. The neutral flux generated during a few
10 milliseconds after the ELM-crash is estimated using the absolutely calibrated D_α -radiance. It is by more
11 than an order of magnitude larger than the puffing rate and dominates the recycling neutral fluxes in the
12 divertor. Different examples indicate that the anomalous overheating of the upper inner divertor tiles that
13 induce the D outgassing is linked to the magnetic configuration and more specifically, to the distance of
14 the plasma Separatrix to the material surfaces.

15 In a final section it is shown, how this local outgassing from the upper inner divertor region induced by
16 the plasma heating could be used to intentionally desorb the accumulated fuel desorption there. This could
17 be useful for wall isotope control and fuel inventory reduction in future JET campaigns with T [29].

18 19 **2. Experimental**

20
21 The here analysed discharges are high-power ($P \geq 15$ MW) H-mode plasmas with plasma current $I_p \geq$
22 1.8 MA and a toroidal magnetic field $B_T \geq 2$ T. We compare always plasma pairs with similar heating
23 power, triangularity and gas injection rate but with different divertor magnetic configuration. More
24 specifically the effect of the proximity of the SPs at the divertor corners near the pumping conducts is
25 compared for similar plasmas as in [6-11].

26 We analyse the visible plasma emission, mainly the D_α -atomic line, to get information of the neutral
27 fluxes. The main diagnostic used is a D_α -spectroscopy system with narrowband-pass filters that views the
28 divertor with 20 chords from an upper port. The radiance is absolutely calibrated and has a temporal
29 resolution of 100 kHz. Also, two spectrometers were used to analyse the D_γ/D_α ratio. Additionally, we
30 also analyse the visible emission with a Fast camera with up to 70 kHz sampling rate [30] and a slow (30
31 Hz) intensified D_α - and D_γ - filtered camera. Both have a tangential view of the divertor [31].

32 To measure the divertor surface temperature the thermal radiation is analysed with a Mid Wave Infrared
33 (MWIR) camera and a Near Infrared Range (NIR) filtered visible camera. The MWIR camera [32, 33]
34 works in the 3-5 μm range and has a sampling rate of about 15 Hz. The exposure times for the here
35 analysed plasmas is of about 0.5 milliseconds. The NIR camera is part of the JET Protection System [34,
36 35]. The camera filters light from the NIR range to extract from the thermal (Blackbody) radiation the
37 surface temperature. The filter is centred at $\lambda = 1016$ nm and has a bandwidth of ± 40 nm. It is absolutely
38 calibrated for $T > 800$ °C and its recording speed is 50 Hz. Unfortunately, other plasma emission sources
39 can contaminate the thermal radiation from Volume plasma emission such as Bremsstrahlung and Free-

1 bound transitions from recombining processes [33]. It should be clarified that the surface emissivity is a
2 free parameter when obtaining the absolute temperature from the thermal emission and depends on the
3 surface properties. Since plasma exposed surfaces can continuously vary their emissivity, a certain
4 uncertainty in the measurement must be kept in mind. Here an emissivity of 0.18 – 0.24 (depending on the
5 temperature range) for the upper inner W-coated carbon divertor tiles was selected. The software
6 framework JUVIL [36] was used to analyse thermal and visible camera videos.

8 **3. Experimental observations at the inner divertor: “Corner” versus “Vertical” configuration**

10 **3.1 Global plasma modifications**

11
12 Figure 1 shows the two divertor magnetic configurations used in discharge #86533. The plasma had
13 following parameters: $B_T = 2.4$ T, $I_p = 2.5$ MA, $P = 17$ MW (NBI) + 1.5 MW (ICRH) and was already
14 analysed in a previous work [6]. During the H-mode, the plasma starts first with the inner SP near the
15 divertor pumping openings (here called Corner or C-configuration) and is moved after 2 seconds to the
16 vertical target (here called Vertical- or V-configuration). Shown are also some inner D_α -chords (cannels 1,
17 3 and 5) and uppermost Langmuir probes (LP). Figure 2 shows several time traces where the strong
18 influence of the divertor magnetic configuration on the plasma parameters can be seen. Plotted are the
19 signals during the H-mode phase of the Neutral Beam Injection (NBI) power, the plasma average density
20 $\langle n_e \rangle$, the pedestal electron temperature T_e , the H_{98Y} confinement factor and the integrated inner and outer
21 divertor D_α -emission radiance $L_{D\alpha}$. The magnetic configuration passes from C- (black arrow) to V-
22 configuration (red arrow) at $t = 9 - 10$ s. The D puffing rate Q_0 was firstly set to 2.5×10^{22} D s⁻¹ and was
23 reduced to 2×10^{22} D s⁻¹ during the V-configuration (it is schematically shown at the upper frame in blue).
24 Note that even with the puffing reduction, $\langle n_e \rangle$ increases. The degradation of the confinement when going
25 to V-configuration is clear: T_e drops significantly and the confinement factor H_{98Y} decreases from 1.05 to
26 0.85. The central electron temperature falls from about 6 to 4 keV (not shown). The divertor plasma also
27 shows considerable changes. During the C-configuration, the global inter-ELM D_α -fluxes are a factor of 3
28 larger at the inner divertor than at the outer. When going to the V-configuration they increase by a factor of
29 3 at the outer and by a factor of 10 at the inner divertor, indicating an enhanced neutral D flux there. The
30 D_α -emission dynamics during the ELMs and its spatial distribution changes will be shown in more detail in
31 the next section. These general trends of the plasma parameter when changing the divertor configuration
32 from Corner- to Vertical- also occur in the plasmas shown in the past [6-11].

34 **3.2 D_α -emission response to divertor magnetic topology changes**

35
36 Figure 3a shows two frames of the divertor taken with the visible Fast camera during the V-
37 configuration of the same plasma #86533: left, before the ELM and right, after the ELM. Below is shown
38 the CAD-view of the camera to the divertor. The coloured lines indicate schematically the different
39 emission regions: in red the outer SP-line, in blue the inner one and in yellow the upper inner divertor

1 region. Note that a strong emission-cloud appears at the high-field-side (HFS) just after the ELM. The
2 accurate localisation of these emission regions where done applying the “Cross-correlation technique”
3 between different ROIs (Region of Interest) of the Fast Camera data and the spatially-well defined D_{α} -
4 chord radiances looking from the upper port to the divertor. The camera had no filter for this discharge but
5 the dominant emission at the divertor is by far D_{α} -atomic line emission. A proof of this is the high cross-
6 correlation yield with the D_{α} -spectroscopy channels once the correct lines were obtained. Also, videos of
7 similar discharges with and without D_{α} -filter are nearly equal, except a higher intensity level without the
8 filter (because of the transmission losses). The camera was operated with 10 μ s exposure time and 25 kHz
9 recording speed.

10 Figure 3b shows two video-clips that can be reproduced by clicking on the frames, above the one of the
11 Corner- and below of the Vertical-configuration. The clips show two ELM cycles, corresponding to about
12 50 ms of plasma time. One of the clips corresponds to a very similar discharge with the same parameters
13 and configuration change as #86533. This is because for the high this framing speed the buffer camera
14 memory limits the video recording time to about two seconds and therefore two consecutive “twin-
15 discharges” were necessary to record the full H-mode period. The movement of the image is due to the
16 ELMs that produce vibrations on the camera supporting structure that is fastened to the Tokamak vessel.
17 Looking to the videos, we see that in the C-configuration, the ELMs are faster and the inter-ELM inter-
18 ELM equilibrium pattern is rapidly recovered. In contrast, in the V-configuration, a strong emission cloud
19 appears at the HFS just after the ELM-crash that dominates in intensity in the whole divertor. This cloud is
20 located at the upper inner divertor region on top of Tiles 0 and 1 as shown in figure 3a.

21 Figure 4a, upper frame, shows for the same discharge the inter-ELM D_{α} -radiance $L^{D\alpha}$ during the
22 configuration change as obtained from the innermost spectroscopy channel that looks to the corner between
23 Tiles 0 and 1 (see figure 1). The intensity increases during the configuration change by a factor of ten.
24 Below is a zoom of the blue frame of the upper figure. It can be seen that in-between ELMs the D_{α} -
25 emission continuously increases (yellow arrows), which makes the inter-ELM intensity monotonically
26 increase during the configuration change (red arrow).

27 The ELM D_{α} -emission dynamics during the stationary phases of the C- ($t < 9$ s) and V- configuration (t
28 > 10 s) is shown in figure 4b for channel numbers 1, 3 and 5 (see figure 1). Below the total inner divertor
29 WI radiance is also shown to visualize the ELM-crashes. The ELM frequency is of about 40 Hz in both
30 phases. In the C-configuration, all D_{α} -channels have positive peaks during the ELM-crash. Also a
31 secondary peak appears for the views that look to the SP. In the V-configuration the emission dynamics
32 completely changes. The innermost two channels that look to the inner upper horizontal divertor (Tiles 0
33 and 1) show strong emission peaks that last about 5 ms longer than the ELM-crash. These correspond to the
34 post-ELM emission cloud seen with the Fast camera. Channel number 3, which looks to the inner divertor
35 corner, shows sometimes no clear spike at the ELM-crash, but the secondary peak as in channel numbers 1
36 and 2 is present. The emission of channel number 5, that looks at inner SP (channel number 5), decreases
37 just at the ELM-crash during about 8 ms (red arrow). These so-called “negative ELMs” are characteristic of
38 a (partly-) recombining, cool and high-density SOL plasma that develops near the SP. Note also that during
39 these periods the WI flux decreases, probably due to the reduced T_e that lowers the sputtering at the targets.

1 When comparing quantitatively all divertor D_α -channels, including the outer ones, we have that in the
2 approximately 5 ms post-ELM period, the contribution from the innermost 3 channels is dominant in the V-
3 configuration. Since the D_α -radiance $L_{D\alpha}$ is absolutely calibrated, the post-ELM neutral D flux F_0 at the
4 upper inner divertor region can be estimated assuming Ionizing conditions there:

$$(1) \quad F_0 = 4\pi A (S/XB) L_{D\alpha},$$

5
6
7
8 where the observing area A corresponds to the projection of the divertor disc of about 12 cm radial
9 extension that is observed by the three innermost chords and the number of ionizations events per photon
10 $S/XB \approx 20$ (see e.g. [22]). We can assume Ionizing conditions since recombination does not contribute at
11 least significantly to the neutral fluxes in this region as is shown in the separate Appendix. From equation
12 (1) we obtain a D neutral flux of about $F_0 \approx 5 \times 10^{23} \text{ D s}^{-1}$ during the post-ELM peak coming from the
13 horizontal upper divertor region covered by the first three D_α -chords. This is a significant quantity, a factor
14 of 25 higher than the puffing rate ($\approx 2 \times 10^{22} \text{ D s}^{-1}$).

15 **3. 3 Correlation of thermal radiation to post-ELM D_α -emission**

16
17
18 The post-ELM neutral fluxes from the upper inner divertor region described in the paragraph above were
19 observed systematically for a large number of high power H-mode plasmas (see later for further examples).
20 As already disclosed in a previous work [21], the origin could be local thermal desorption due to the power
21 deposited by the ELMs. In fact, the observed D_α -emission location on top of Tiles 0 and 1 coincides with
22 the region where most D containing Beryllium co-deposits accumulate, as deduced from surface analysis
23 studies [37, 38]. If this is true, in order to generate the outgassing of trapped D, an increased power load
24 must occur that overheats the surfaces at this region that should be correlated with the observed local
25 increased D_α -emission. Moreover, if this correlation is found, it would be interesting to understand the
26 cause of this local overheating, most probably linked to the magnetic divertor configuration. These points
27 will be analysed first in this section for the plasma described above.

28 For the discharge #86533 analysed above, unfortunately the MWIR thermography camera looking to the
29 inner divertor was not operative. We therefore studied the data from a NIR Protection Camera that looks
30 tangentially with a similar view as the Fast Visible Camera. As disclosed in Section 2, these kind of
31 cameras are only calibrated for very high temperatures $T > 800 \text{ }^\circ\text{C}$. Additionally, in many situations, other
32 emission sources contaminate the thermal radiation filtered at this range, such as plasma Bremsstrahlung
33 and emission due to atomic Free-bound transitions from recombining processes. This contamination can be
34 even dominant especially in cool high-density plasma conditions as will be shown. Figure 5a shows a video
35 clip of this NIR camera during the H-mode phase of plasma #86533 (*click on the frame to reproduce the*
36 *video*). The light intensity is in arbitrary units, i.e. without calibration. The transition from the C- to the V-
37 configuration takes place at about $t = 6 \text{ s}$ of the clip. The change in the emission pattern is clear. During the
38 C-configuration, light at the inner divertor comes only from a narrow region corresponding to the SP line.
39 When passing to the V-configuration, this emission cloud expands and becomes stronger, while brilliant
40 emission regions appear on top of Tile 1. The origin of the toroidal emission cloud is volume plasma

1 emission characteristic of a dense and cool plasma, but the light from the bright discrete areas with sharp
2 contours at Tile 1 is mainly surface thermal emission indicating local overheating (Hot Spots). In Figure 5b
3 the upper pictures show two frames of the same video (in false colour scale), left in C- and right in V-
4 configuration. A Region of Interest (ROI) has been selected on top of Tile 1 around one of these hot spots
5 and the time evolution of the average intensity in this ROI is represented below. The time trace shows a
6 clear increase when the configuration changes from Corner to Vertical indicating a local temperature raise.

7 Since due the light contamination a quantitative estimation of the surface temperature is not possible for
8 this plasma with the NIR Protection camera, another similar plasma of the same experiment was selected
9 for which data of the MWIR thermography camera were available. Discharge #84641 has a very similar
10 divertor configuration change as the one analysed before (#86533), although with 3 MW less NBI power,
11 no ICRF power and also somewhat lower B_T and I_p . Figure 6a shows a frame of the MWIR camera for this
12 discharge and below is a zoom of the divertor. Two ROIs were selected at Tiles 0 and 1. The time evolution
13 of the maximum temperature of both ROIs is shown in figure 6b during the H-mode, the arrows indicating
14 the C- and V-configuration phases. A clear raise of the base-temperature, from about 200-250 °C to 300-
15 400 °C is visible at Tiles 0 and 1 when the configuration changes to V. Additionally strong temperature
16 spikes appear at Tile 1 reaching values > 700 °C. Only a few ELM-crashes (duration time is ≈ 1 ms) are
17 randomly captured by the camera because its long “dead time” without data. In other words: since the time
18 between two consecutive frames is 65 ms but the sensor exposure time just 0.6 ms only a fraction of ELM-
19 crash events, that appear every 25 ms approximately, are captured. It should be noted that higher
20 temperatures should be expected for the discharge analysed before (#86533), since the heating power was
21 higher.

22 On the other hand, laboratory measurements by Thermal Desorption Spectroscopy (TDS) have shown
23 that the outgassing of D trapped in Beryllium co-deposits happen at discrete characteristic temperatures,
24 which begin with a strong desorption peak at about 300 - 350 °C [39, 40]. This values seem to be reached
25 and even well surpassed during ELMs at Tiles 0 and 1 during the V-configuration phase. We can therefore
26 say that, at least potentially, during this plasma phase D may be desorbed from the Beryllium co-deposits.
27 It should be however remembered that, due to the possible error in the temperature estimation (see section
28 2), this point should be confirmed in future studies as discussed later.

29 Once it is confirmed that for certain high-power H-mode plasmas the threshold temperature for D
30 outgassing is very probably reached and surpassed at Tiles 0 and 1, it would be interesting to understand
31 the origin of this anomalous overheating. Initially, when looking to the magnetic configuration change of
32 the analysed plasma (figure 1), it was surprising, that a relatively small change of the inner SP position
33 relative to the distance to the upper inner divertor region could produce such an increased surface heating
34 where the D emission is observed. Also the modification of the ELM characteristics when changing the
35 configuration cannot explain the increased heat load. Neither the ELM frequency nor the ELM energy-
36 loss (depicted from the pedestal T_e and n_e decays as well from the WI emission peak intensities) varied
37 significantly with the configuration change. The only possible reason found for this temperature raise is
38 following: when turning to V-configuration, the Clearance (or Gap) to the upper inner divertor corner at
39 Tile 1, defined as the distance from the material surface to the Separatrix, was significantly reduced due
40 to a change of the outer SP position. This can be seen in figure 1, where the respective Clearances are

1 marked with a blue arrow for the V-configuration (about 6 cm) and a red one for the C-configuration
2 (about 12 cm). Assuming a typical SOL power decay length $\lambda_q = 3$ mm for high-power H-mode plasmas
3 in JET at the outer midplane and taking into account the magnetic flux expansion at the upper inner
4 divertor, which is the same for both configurations, we get that the heat flux becomes amplified there by a
5 factor of about 30 in the V-configuration with the reduced Clearance.

6 On the other hand, it is well-known that co-deposits reach much higher temperatures compared to the
7 the bulk material on which they are deposited due to their low thermal conductivity [41-44]. In fact, they
8 appear as glowing “Hot Spots” and can be distinguished quite easily from the bulk material even with
9 visible cameras. This effect should also facilitate an enhanced overheating of these surfaces.

11 4. Other examples

13 To confirm the link between Clearance at the upper inner divertor with the increased surface heating and
14 the enhanced D_α -emission there, other plasmas have been analysed. Figure 7a shows the divertor
15 configuration of #92121, where the position of the outer SP was changed along the outer Horizontal target
16 during the H-mode phase. Note that in this case the inner SP was laid still at the vertical Tile 3. While
17 doing this, the Clearance to the corner of Tile 1 was reduced from 10 to 6 cm approximately. The gas
18 puffing rate and the NBI power ($P = 14$ MW) was maintained constant. Here the only significant global
19 plasma variation after the configuration change to a reduced Clearance was a 10% increase in plasma
20 density and also a rise of the ELM frequency from 60 to 80 Hz. Concerning the thermal and D visible
21 emission changes we see following. Figure 7b shows two images that are an average of ten frames
22 corresponding to about 180 ms from the NIR Protection camera for the same discharge (again no MWIR
23 camera available), left before and right after the Clearance decrease. The raise of the thermal emission from
24 Hot Spots clearly indicates an increased power load there when the Clearance is reduced. Below in figure
25 7c are the images of a D_γ -filtered camera averaged over 200 ms with the same view (D_α was not available).
26 Despite the unchanged inner SP position the emission distribution clearly changes: before the Clearance
27 reduction the dominant D emission at the inner divertor comes from the lower part of the vertical target
28 near the inner SP position and after from the top of Tile 1. Figure 7d shows the time evolution of the
29 innermost divertor Spectroscopy D_α -emission chord (channel number 1) looking on top of Tiles 0 and 1.
30 An increase of the base level (inter-ELM) during the Clearance reduction by a factor of about 6 is observed.
31 At the same time (not shown), the equivalent channels of BeII and WI raise just by a factor of 2, as also
32 does the ion saturation current of the innermost divertor Langmuir Probe on Tile 1 (see figure 1). This
33 indicates that the Clearance reduction induces in this region an increase of the ion flux by a factor of about
34 2 while that of the D_α -emission is three times larger. Since a sensible increase of S/XB cannot be expected,
35 this means that the neutral flux is strongly enhanced with respect to the incoming ion flux that points again
36 to local thermal desorption there. Figure 7e shows the clear displacement of the D_α -emission peak to the
37 top of Tile 1 (channel number 2) during the inter-ELM period as obtained from the upper spectroscopy
38 lines of view in agreement with the D_γ -filtered camera (figure 7c).

39 Another similar example of Clearance reduction without inner SP position change but where the MWIR
40 thermography camera was available is shown in figure 8a. The two equivalent discharges #83177 and

1 #83491 had following parameters: $B_T = 2.8$ T, $I_p = 2.5$ MA, $P=16$ MW (NBI). They were already compared
2 in another work to see the effect when changing the outer SP from the horizontal to the vertical target [45].
3 The average images of the IR thermography video over 1 second (about 15 frames) of both plasmas during
4 the H-mode of both discharges are shown to the right. For the plasma with reduced Clearance the
5 temperature at Tiles 1 and 0 is of about of $300 - 350$ °C, much higher than the other one that just reaches
6 about 200 °C. Figure 8b shows the inter-ELM D_α -emission distribution at the inner divertor (1 is innermost
7 channel) for both discharges. The strong increase of the intensity for the reduced Clearance plasma from
8 Tile 1 is again clearly visible.

9 The last case study compares three plasmas with following parameters: $B_T = 2.2$ T, $I_p = 2$ MA, $P = 13.5$
10 MW (NBI) + 1.5 MW (ICRF). As shown in figure 9a, two of them had both SPs at the divertor although
11 different puffing levels. In the third one the inner SP was moved to the vertical target. Note that the
12 interesting point here is that the Clearance to the upper inner divertor corner is not varied, only the inner SP
13 position. These plasmas were already analysed to study the influence of divertor neutral pumping
14 optimisation and gas injection rate on plasma edge properties and global plasma confinement at high
15 triangularity [10]. The best confinement ($H_{98Y} \approx 1$) was achieved for the lowest puffing level (lowest
16 pedestal density) and both SPs at the divertor corners (#89341). Stable plasmas with the inner SP at the
17 vertical target with such low gas injection rates were not possible to maintain due to the high tungsten
18 influx. This was only possible in discharge #89340 when the gas level was duplicated, that had the same
19 level as #89334. In both plasmas the confinement degraded in by about 20% independently of the divertor
20 configuration. Their pedestal densities were similar, although the ELM showed quite different
21 characteristics [10], being much longer as in a quiescent H-mode for #89340. Making a similar analysis for
22 this set of plasmas as done above we observe following. The NIR protection camera showed that for
23 increasing puffing levels, at the inner divertor an increasingly strong volume emission evolves, indication
24 of the characteristic cool-high density recombining SOL plasma, this happening at a similar degree in the
25 C- (#89334) and the V-configuration (#89340). However, no “Hot spots” are visible in none. The MWIR
26 camera shows similar temperatures at Tiles 0 and 1 for both configurations. Additionally, as shown in
27 figure 9b, the inter-ELM D_α -emission distribution at the inner divertor is very similar for the three plasmas.
28 The one with the lowest puffing is by a factor of about 3 lower than the other two, which have similar
29 intensities despite the different divertor configurations. There is no enhanced D_α -emission at the upper
30 inner divertor for the plasma in the V-configuration here. Therefore it can be said that, moving the inner SP
31 position from the divertor corner a few centimetres up on the vertical target, without Clearance
32 modification, does not sensibly modify the neutral flux distribution.

33 34 **5. Using plasma configuration to induce fuel desorption from the upper inner divertor**

35
36 It is well known that the plasma Hydrogen isotope is not only composed of that injected by puffing to
37 the plasma or by NBI, but also of the ones trapped in the reactor surface walls and re-enter into the
38 plasma during recycling. This is called “Wall isotope exchange”. This process is used intentionally as a
39 Wall-conditioning technique to clean-up the reactor vessel. It has been already used in TFTR and JET to
40 retrieve the trapped T from the walls after D-T experiments with repetitive low power plasmas [46-49].

1 Separatrix scanning with high power plasmas has been also proposed elsewhere [50]. Wall isotope
2 exchange has been also extensively studied using ICRF discharges with only toroidal magnetic fields to
3 apply it to future superconducting reactors such as ITER [51-53]. A review on the different Wall-
4 conditioning techniques proposed for ITER can be found in [54].

5 More recently, dedicated experiments of isotope exchange in JET with ITER-like wall using Ohmic
6 and low-power L-mode plasmas showed a very weak access to the long-term retention reservoir in the co-
7 deposited Beryllium layers where most of the fuel becomes trapped [55]. Therefore alternative techniques
8 to clean up the retained T in JET would be desirable. As already mentioned, it is known that fuel trapped
9 in Beryllium co-deposits in the divertor can be removed by heating the surface to temperatures $> 300 -$
10 $350\text{ }^{\circ}\text{C}$ [37, 38]. Unfortunately, such high temperatures can be reached by baking of the vacuum vessel in
11 only marginally. Therefore, specific Wall-conditioning techniques are proposed to prepare the next JET T
12 campaigns with the ITER-like wall [56]. One of the proposed techniques is linked to the subject-matter of
13 the present work, since the local outgassing from the Be co-deposits at the upper inner divertor is
14 intentionally induced by plasmas with magnetic configurations that focalise the ion and heat fluxes there.
15 A preliminary analysis is shown in this section.

16 The discharge described here corresponds to a plasma from the beginning of a D campaign just after an
17 H one. Figure 10a shows the magnetic configuration of the high-power plasma #91961 with $B_T = 3\text{ T}$, $I_p =$
18 3.2 MA and $P = 24\text{ MW}$ (NBI). It was used to study W melting at Tile 5 by directing the outer SP there.
19 The inner SP was raised at the upper corner of Tile 1 and the Clearance there was quite small (6 cm).
20 Figure 10b up corresponds to a frame of the MWIR thermography camera during the NBI-phase and where
21 two ROIs are defined corresponding to Tiles 0 and 1. Below, the corresponding temperature evolutions are
22 shown. The ROI corresponding to Tile 1 overpasses the camera settings saturation value with $T > 1100\text{ }^{\circ}\text{C}$
23 (note that half the value is shown) and the one of Tile 0 reaches $600\text{ }^{\circ}\text{C}$. For these very high temperatures a
24 strong outgassing at the upper inner divertor region has to be expected.

25 Figure 11 shows following time traces for this discharge: the NBI power P , the D puffing rate Q_0 , the
26 pressure measured in the lower sub-divertor duct p , the vertical coordinate of the inner SP Z_{SP} and the
27 innermost D_{α} chord $L_{D\alpha\text{ in}}$. Q_0 has at the beginning a pulse (marked with a circle) to achieve the desired
28 plasma density for the H-mode and later stays constant at a moderate value. The corresponding increase of
29 the pressure p to this puffing pulse is marked with a first red arrow. There is a time delay of p with respect
30 to the puffing pulse due to the conductance of the tokamak vacuum vessel to the manometer location, that
31 is quite far. The inner SP is raised at $t \geq 12\text{ s}$, when Z_{SP} increases as marked with a second circle. Despite
32 the constant puffing level, the neutral pressure shows a second increase with a similar time delay as before.
33 Also at this moment, the surface temperatures of Tiles 0 and 1 sharply raise (figure 10b). At the same time
34 the innermost D_{α} flux strongly increases and even saturates ($L^{D\alpha} > 4 \times 10^{17}\text{ ph s}^{-1}\text{ cm}^{-2}\text{ sr}^{-1}$), this indicating
35 a strong recycling/outgassing source at the upper inner divertor as we expected before.

36 The here analysed discharge was one of the first high power plasmas of a D campaign just after a long H
37 campaign and one could expect that H isotope was accumulated in the Beryllium co-deposits of Tiles 0 and
38 1. Therefore, if local heating and fuel outgassing was achieved by this D plasma, than some accumulated H
39 isotope should have been desorbed. The lowest frame of figure 11 shows the time trace of the H isotope
40 concentration ($H/(H+D)$) of the plasma as measured by an optical Penning gauge in the sub-divertor. There

1 is a clear increase of this signal, that reached up to about 10% during the phase when Tiles 0 and 1 were
2 heated due to the inner SP raise. Note that before this, the H-concentration is $\leq 3\%$, which is below the
3 detection limit. This is a clear indication that the plasma configuration with the raised inner SP was
4 effective in desorbing trapped H at the upper inner Divertor region.

5 Future studies are planned before the next T campaign to try to confirm the potential use of this local
6 plasma heating and outgassing effect at the upper inner divertor as a Wall-conditioning technique for JET
7 [50]. For the next T-T experiments, it is desired to remove all possible trapped D from the walls of previous
8 campaigns, to minimise D-T fusion reactions. A H-campaign has been foreseen before the T one, to
9 exchange as much as possible H by the previously trapped D. In this phase, the use of raised inner SP
10 configurations to induce heating of Tiles 0 and 1 will be studied in more detail. If useful, the same
11 technique could be later applied to recover surface retained T at this region.

12

13 **6. Discussion and Summary**

14

15 In the present work we have studied some aspects concerning the impact of the divertor configuration on
16 recycling neutral fluxes for JET ITER-like wall high power H-mode plasmas. We analyse in detail the
17 previously observed anomalously strong D_α -emission [22] that appears at the upper inner divertor for
18 certain magnetic topologies. For these plasmas, a systematic correlation has been found of this enhanced
19 emission with a local surface temperature raise there. Since this region is where the thickest fuel containing
20 Be co-deposits accumulate, we believe that surface overheating of these are the origin of the outgassing. In
21 fact, the measured surface temperatures locally exceed the typical thermal D release from this kind of
22 layers ($T > 350$ °C). The D emission happens just after the ELM-crash for a period of typically 5
23 milliseconds. Its flux was quantified and dominates over puffing and the rest of recycling during this period
24 of the ELM-cycle.

25 We propose that the origin of the local increased surface temperature for these plasma configurations is
26 the increased heat flux due to the reduced distance from inner upper divertor corner to the Separatrix
27 (Clearance). Additionally, it is well-known that co-deposits reach more easily higher temperatures
28 compared to the to the bulk material on which they are deposited due to their low thermal conductivity. It
29 must be however acknowledged, that there is a considerable uncertainty in the present absolute surface
30 temperature measurements. This is because the co-deposits on top of the W-coated carbon Tiles 0 and 1
31 most probably alters the estimated thermal surface emissivity, which is a fundamental parameter to deduce
32 the temperature. Future work is on going to experimentally measure the emissivity more accurately there.

33 On the other hand it should be noted that the Clearance reduction at the upper inner divertor may have
34 additional effects apart from those described in the present work. It seems obvious to believe that the
35 coupling between the divertor SOL and the confined pedestal plasma region will be facilitated. For
36 example, the penetration probability inside the Separatrix of the neutrals (fuelling efficiency) coming from
37 this region will be increased due to the shorter path. Also the SOL radiation layer, which generally
38 dominates at the inner divertor region close to the X-point, has a shorter distance to approach and even
39 penetrate into the confined pedestal plasma region (perhaps inducing its cooling). Summarising, the
40 Clearance reduction at the upper inner divertor may, additionally to the effects described in the present

1 work, also affect the coupling of the inner divertor SOL plasma with the confined pedestal region that
2 should be taken into account when analysing the effect of the magnetic topology.

3 Finally, we have studied high-power plasmas with raised inner SP at the upper inner divertor corner to
4 intentionally induce previously trapped D by thermal outgassing. The intention is to use this as a fuel
5 recovery technique at regions where Be co-deposits accumulate. By focalising the plasma ion and heat flux
6 there, very high temperatures can be achieved ($T > 1000$ °C) and as expected, strong D desorption from this
7 region was observed. The shown preliminary analysis indicates that these plasmas can be used for Wall
8 isotope exchange and T recovery specifically in this reactor vessel region, complementarily to other Wall-
9 Conditioning techniques [56]. More specific experiments are planned in the next future to continue this
10 study and optimise the plasma parameters (power, magnetic shape, density, etc) for maximum conditioning
11 efficiency.
12

13 Acknowledgement

14 This work has been carried out within the framework of the EURO fusion Consortium and has received
15 funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053.
16 The views and opinions expressed herein do not necessarily reflect those of the European Commission.
17

18 References

- 19
20 [1] S Brezinsek et al. 2013 *Nucl. Fusion* 53 083023
21 [2] G F Matthews et al. 2014 *Phys. Scr.* T159 014015
22 [3] F Romanelli on behalf of JET Contributors 2015 *Nucl. Fusion* 55 104001
23 [4] X Litaudon et al. 2017 *Nucl. Fusion* 57 102001
24 [5] C Giroud et al. 2013 *Nucl. Fusion* 53 113025
25 [6] E de la Luna et al. 2014 25th IAEA FEC, Saint Petersburg, Russia
26 [7] E Joffrin et al. 2014 25th IAEA FEC, Saint Petersburg, Russia
27 [8] E Solano et al. 2014 *Proc. 41st EPS Conference on Plasma Physics*, Berlin, Germany
28 [9] P Tamain et al. 2015 *J. Nucl. Mat.* 463 450
29 [10] E de la Luna et al. 2016 IAEA FEC 2016
30 [11] E Joffrin et al. 2017 *Nucl. Fusion* 57 086025
31 [12] S Kaye et al. 1984 *J. Nucl. Mater.* 121 115
32 [13] L.D. Horton et al. 1999 *Nucl. Fusion* 39 1
33 [14] A Loarte 2001 *Plasma Phys. Control. Fusion* 43 R183
34 [15] A S Kukushkin et al. 2005 *Nucl. Fusion* 45 608
35 [16] S Brezinsek et al. 2015 *J. Nucl. Mat.* 463 11
36 [17] M Groth et al. 2013 *Nucl. Fusion* 53 093016
37 [18] A Järvinen et al. 2013 *Proc. 40th EPS Conf. on Plasma Physics*, Espoo, Finland.
38 [19] S Wiesen et al. 2016 *Contrib. Plasma Phys.* 56 754
39 [20] D M Harting et al. 2015 *J. Nucl. Mat.* 463 493

- 1 [21] S Brenzisek et al. 2016 *Phys. Scripta* T167 014076
2 [22] S Wiesen et al 2017 *Nucl. Fusion* 57 066024
3 [23] C Guillemaut et al. 2018 *Nucl. Fusion* 58 066006
4 [24] E Marenkov et al. 2012 *Phys. Plasmas* 19 092501
5 [25] A Yu Pigarov et al. 2014 *Phys. Plasmas* 21 062514
6 [26] E de la Cal and the TJ-II Team 2015 *Plasma Phys. Control. Fusion* 57 075001
7 [27] K Schmid 2016 *Phys. Scripta* T167 014025
8 [28] V S Neverov et al. 2019 *Nucl. Fusion* 59 046011
9 [29] L Horton et al. 2016 *Fusion Eng. Design* 109–111 925
10 [30] E de la Cal et al. 2012 *Proc. 39th EPS Conf. on Plasma Physics* (Stockholm, Sweden)
11 [31] A Huber et al. 2012 *Rev. Sci. Instr.* 83 10D511
12 [32] E Gauthier et al. 2007 *Fusion Eng. Design* 82 1335
13 [33] I Balboa et al. 2016 *Rev. Sci. Instr.* 87 11D419
14 [34] G Arnoux et al. 2012 *Rev. Sci. Instr.* 83 10D727
15 [35] A Huber et al. 2017 *Phys. Scripta* T170 014027
16 [36] V Huber et al. 2017 *Fusion Eng. Design* 123 979
17 [37] M Mayer et al. 2016 *Phys. Scr.* T167 014051
18 [38] A Widdowson et al. 2017 *Nucl. Fusion* 57 086045
19 [39] D Alegre et al. 2017 *Physica Scripta* T170 014028
20 [40] G De Temmerman et al. 2017 *Nucl. Mat. Energy* 12 267
21 [41] P H LaMarche et al. 1986 *J. Vac. Sci. Tech.* A 4 1198
22 [42] E Gauthier et al. 2005 *J. Nucl. Mat.* 337–339 960
23 [43] J Gaspar et al. 2016 *Int. J. Thermal Sci.* 104 292
24 [44] R Mitteau et al. 2006 *Nucl. Fusion* 46 S49
25 [45] M J Leyland et al. 2015 *Nucl. Fusion* 55 013019
26 [46] L D Horton et al. *J. Nucl. Mat.* 196-198 139-142
27 [47] P Andrew et al. 1992 *J. Nucl. Mater.* 196-198 143
28 [48] C H Skinner et al. 1997 *J. Nucl. Mat.* 241-243 214
29 [49] P Andrew et al. 1999 *Fusion Eng. Design* 47 233
30 [50] S Higashijima et al. 1999 *J. Plasma Fusion Res.* 75 1297 (in Japanese)
31 [51] E de la Cal and E Gauthier 1997 *Plasma Phys. Control. Fusion* 39 1083
32 [52] D Douai et al. 2011 *J. Nucl. Mat.* 415 S1021
33 [53] T Wauters et al. 2011 *J. Nucl. Mat.* 415 S1033
34 [54] M Shimada et al. 2011 *J. Nucl. Mat.* 415 S1013
35 [55] T Loarer et al. 2015 *Nucl. Fusion* 55 043021
36 [56] I Borodkina et al. 2018 *Proc. 45th EPS Conf. on Plasma Physics* O2.106, Prague, 2018
37 [57] G M McCracken et al. 1998 *Nucl. Fusion* 38 619

38

39 **Appendix**

40

41 The use of equation (1) to estimate the D neutral flux F_0 through the D_α -radiance $L_{D\alpha}$ can be only used if
42 the plasma is in Ionizing conditions, i.e. recombination can be neglected. This has been checked to be the
43 case here in two ways:

1 1. The ion flux of the upper Langmuir probe (see figure 1) estimated from the ion saturation has a
2 similar value (within a factor of two) than the neutral flux obtained locally from D_{α} -channel number 3, that
3 looks very near to this probe. When the measured ion and neutral fluxes are similar, it means that recycling
4 dominates over recombination.

5 2. It is known that in low temperature, high density recombining plasmas, the ratio of the Balmer lines
6 D_{γ} / D_{α} increases from about 0.02 in Ionizing conditions to about 0.1 in Recombining conditions [57].
7 This ratio was monitored using two visible Spectrometers that collect the light of both atomic lines with the
8 same lines of view as the fast D_{α} -Spectroscopy. Unfortunately their time resolution is of about 40 Hz so
9 that the signals are ELM-averaged. When looking to the Spectrometer channels that look to the upper inner
10 divertor corner we obtain a ratio $D_{\gamma} / D_{\alpha} \approx 0.03$ along the whole H-mode phase (in C- and V-
11 configuration), which is approximately the one expected in Ionizing conditions.

12

13

Figure Captions

Figure 1: Divertor magnetic configurations of plasma #86533 showing the Corner (C) and Vertical (V) configurations. Shown are also some inner D_α -channels and Langmuir probes (LP).

Figure 2: Time traces of the NBI power P , puffing rate Q_0 , plasma average density $\langle n_e \rangle$, pedestal electron temperature T_e , the H_{98Y} confinement factor and the integrated inner and outer divertor D_α -emission radiance L_{D_α} . The arrows at the horizontal axis mark the C- and V-configuration phases.

Figure 3: a) Two frames of the divertor taken with the visible Fast camera during the V-configuration of #86533: left before the ELM and right after the ELM and below the CAD view of the camera to the divertor (see text). b) Corresponding video-clips of the Corner- (up) and the Vertical-configuration (down), (*click on the frame to reproduce the video*).

Figure 4: a) Inter-ELM level evolution of the innermost D_α -channel radiance L^{D_α} looking to the corner between Tiles 0 and 1. b) Time traces of D_α - radiance of channels 1, 3 and 5 (see Figure 1) and total inner divertor WI radiance during C- (up) and V-configuration (down).

Figure 5: a) Video clip of NIR camera during the H-mode phase of #86533 (*click on the frame to reproduce the video*). b) Upper pictures show two frames of the same video (in false colour scale), left in C- and right in V-configuration and below the time evolution of the average intensity of the selected ROI.

Figure 6: a) Wide-angle view of the MWIR camera for plasma #84641 and below a Zoom of the divertor where two ROIs at Tiles 0 and 1 are shown. b) Time evolution of the maximum temperature of the selected ROIs during the H-mode, the arrows indicating the C- and V-configuration phases.

Figure 7: a) Divertor configuration of #92121 and b) two averaged images of the NIR camera and c) D_γ -filtered camera. The left and right images correspond respectively to the larger and shorter Clearance phases. d) Time evolution of the innermost divertor Spectroscopy D_α -emission chord looking to Tiles 0 and 1. e) D_α -emission profiles as a function of channel number and major radius R .

Figure 8: a) Magnetic configurations of plasmas #83177 and # 83491 and to the right, two frames of each of the MWIR. b) Inter-ELM D_α -emission profiles at the inner divertor of both plasmas.

Figure 9: a) Magnetic configurations of plasmas #89341, #89334 and #89340 and b) inter-ELM D_α -emission distribution at the inner divertor.

1 **Figure 10:**a) Magnetic configuration of plasma #91961 and b) frame of the MWIR thermography camera
2 during the NBI-phase where two ROIs are defined corresponding to Tiles 0 and 1 and below, their
3 corresponding temperature evolutions (note that the half value is shown for Tile 1).

4

5 **Figure 11:** Time traces of plasma #91961: NBI power P , puffing flux Q_0 , pressure measured in the sub-
6 divertor p , vertical coordinate of the inner SP Z_{SP} , the innermost D_{α} chord $L_{D\alpha in}$ and Hydrogen
7 concentration $H/(H+D)$.

8